



Drawing **0035**

Description **1/8 fixed Valve with knob Screw**

ASSEMBLY INSTRUCTION:

Insert the item into the radiator connector and rotate it until the O-ring is adherent to the outside surface of the connector.

Make sure that the O-ring adheres to the flat surface of the connector and is not ejected from the seat.

Even if the valve can withstand a tightening torque of 10 Nm, do not exceed the maximum recommended tightening torque of 8 Nm to prevent the O-ring from being ejected from the seat, cut or permanently deformed.

The connected part must comply with DIN 76-2

COMPONENTS:

BODY, SCREW: BRASS UNI EN 12164 CW614N - NICKEL-PLATING 3-5 MICRON

O-RINGS: EPDM 70SH BLACK

TECHNICAL NOTES:

BODY MAX TIGHTENING TORQUE: 10 Nm;

SUGGESTED TIGHTENING TORQUE: 8 Nm

SCREW TIGHTENING TORQUE FROM 0,8 TO 2 Nm

CAP ROTATION TORQUE: 3 Nm

OPERATING TEMPERATURE: 80°C (PEAK: 130°C)

HIGHEST WORKING TEMPERATURE: 130 °C for 60 sec

OPERATING PRESSURE: 4bar (Peak: 13 BAR)