



Drawing **0888**

Description **Water drain Tap flow min 30 l/h**

ASSEMBLY INSTRUCTION:

Insert the item into the radiator connector and rotate it until O-ring is adherent to the outside surface of the connector.

Make sure that the O-ring adheres to the flat surface of the connector and is not ejected from the seat.

Even if the plug can withstand a tightening torque of 35 Nm, do not exceed the maximum recommended tightening torque of 10 Nm to prevent the O-ring from being ejected from the seat, cut or permanently deformed.

The connected part must comply with DIN 76-2

COMPONENTS:

BODY AND SCREW: BRASS UNI EN 12164 CW614N - NICKEL-PLATING 3-5 MICRON

O-RING: EPDM 70SH BLACK

PLASTIC: NYLON 6 WHITE

TECHNICAL NOTES:

BODY MAX TIGHTENING TORQUE: 35 Nm;

SUGGESTED TIGHTENING 10 Nm

SCREW TIGHTENING TORQUE FROM 0,8 TO 2 Nm

PLASTIC ROTATION TORQUE: 3 Nm

OPERATING TEMPERATURE: 80°C (PEAK: 130°C)

OPERATING PRESSURE: 4bar (Peak: 10 BAR)

DRAINING FLOW: 100 l/h AT 2 Bar WITH 1 TURN OPENED SCREW



Drawing **0889**

Description **Water drain Tap flow min 30 l/h**

ASSEMBLY INSTRUCTION:

Insert the drain valve into the radiator connector and rotate it until the O-Ring is adherent to the outside surface of the connector. Make sure that the O-ring adheres to the flat surface of the connector and is not ejected from the seat. Even if the plug can withstand a tightening torque of 15 Nm, do not exceed the maximum recommended tightening torque of 10 Nm to prevent the O-ring from being ejected from the seat, cut or permanently deformed.

The connected part must comply with DIN 76-2."

COMPONENTS:

BODY AND SCREW:BRASS UNI EN 12164 CW614N

- NICKEL-PLATING 3-5 MICRON

O-RING:EPDM 70SH BLACK

PLASTIC: NYLON 6 WHITE

TECHNICAL NOTES:

BODY MAX TIGHTENING TORQUE: 15 Nm;

SUGGESTED TIGHTENING 10 Nm

SCREW TIGHTENING TORQUE FROM 0,8 TO 2 Nm

UTILIZATION TEMPERATURE: 80°C (PEAK: 130°C)

UTILIZATION PRESSURE: 4bar (Peak: 13 BAR)

DRAINING FLOW: 100 l/h AT 2 Bar WITH 1 TURN OPENED SCREW



Drawing **88812**

Description **Water drain Tap flow min 30 l/h**

ASSEMBLY INSTRUCTION:

Insert the drain valve into the radiator connector and rotate it until the O-Ring is adherent to the outside surface of the connector. Make sure that the O-ring adheres to the flat surface of the connector and is not ejected from the seat. Even if the plug can withstand a tightening torque of 35 Nm, do not exceed the maximum recommended tightening torque of 10 Nm to prevent the O-ring from being ejected from the seat, cut or permanently deformed.

The connected part must comply with DIN 76-2.

COMPONENTS:

BODY AND SCREW: BRASS UNI EN 12164 CW614N

NICKEL-PLATING 3-5 MICRON

O-RING: EPDM 70SH BLACK

PLASTIC: NYLON 6 WHITE

TECHNICAL NOTES:

BODY MAX TIGHTENING TORQUE: 35 Nm;

SUGGESTED TIGHTENING TORQUE: 10 Nm

SCREW TIGHTENING TORQUE FROM 0,8 TO 2 Nm

PLASTIC HEAD ROTATION TORQUE Max 3 Nm

OPERATING TEMPERATURE: 80°C (PEAK: 130°C)

OPERATING PRESSURE: 4bar (Peak: 12 BAR)

DRAINING FLOW: 100 l/h AT 2 Bar WITH 1 TURN OPENED SCREW